

NXG-PI-QAM-S

Secure Pro:Idiom® Encryption Module for QAM (MPTS)



Key Features

- » Adds digital content protection for QAM video delivery
- » Supports SPTS format
- » Reliable, secure way to protect digital HD content
- » Supports up to 144 programs w/ Pro:Idiom® license

Product Overview

The **NXG-PI-QAM-S** inputs MPEG-compliant transport streams through the NXG IP backplane to add Pro:Idiom encryption to a multiple program transport stream (MPTS) format. The Pro:Idiom encrypted video content is routed via the NXG IP backplane to the desired QAM outputs for distribution. The NXG-PI-QAM is designed for compatibility with only the NXG QAM Modulator module.

The Pro:Idiom encryption is compatible with existing Pro:Idiom decryption devices, such as TV and set-top-boxes most commonly used in Hospitality locations.

Ordering Information

Model	Stock #	Description
NXG-PI-QAM-S	6793 QS	Secure Pro:Idiom® Encryption Module for QAM (MPTS); 72 Programs
NXG-PI-LIC	6779	License to add 72 more programs for a total of 144

NXG-PI-QAM-S

Secure Pro:Idiom® Encryption Module for QAM (MPTS)

Module Specifications

Input

IP	2.2 Gb Clear MPTS from QAM Modulator module
----	---

Output Encoding

IP	2.2 Gb Pro:Idiom® MPTS to QAM Modulator module
----	--

General

Dimensions (W x H x D)	1.15 x 15.5 x 7.0 in (29 x 394 x 178 mm)
------------------------	--

Power	DC via NXG Mainframe Backplane
-------	--------------------------------

Power Consumption	13 W
-------------------	------

Weight	2.0 lbs (0.9 kg)
--------	------------------

Operating Temp.	32 to 122 °F (0 to 50 °C)
-----------------	---------------------------

Storage Temp.	-13 to 158 °F (-25 to 70 °C)
---------------	------------------------------

Operating Humidity	0 to 95% RH @ 35 °C max, non-condensing
--------------------	---

Alarms & Monitoring

Front Panel	1x Status LED (Bicolor)
-------------	-------------------------